

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 November 2003 (27.11.2003)


PCT

(10) International Publication Number
WO 03/098003 A1

- (51) International Patent Classification⁷: F01B 31/08, 31/10
- (21) International Application Number: PCT/US03/15560
- (22) International Filing Date: 15 May 2003 (15.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/380,637 15 May 2002 (15.05.2002) US
- (71) Applicant (for all designated States except US): DELTA-HAWK, INC. [US/US]; 10698 South 76th Street, Franklin, WI 53132 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): DOERS, Douglas, A. [US/US]; 10698 South 76th Street, Franklin, WI 53132 (US).
- (74) Agents: PRICE, David, R. et al.; Michael Best & Friedrich LLP, 100 East Wisconsin Avenue, Milwaukee, WI 53202 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A LUBRICANT-COOLED AND WRISTPIN LUBRICATING PISTON



(57) Abstract: A piston for an internal combustion engine including a skirt (32) and a crown (34). The skirt includes a top portion (48) and a cylindrically-shaped wall portion (50) extending from the top portion defining a skirt cavity (82). The top portion includes upper and lower surfaces. The lower surface is configured to define a bearing surface (72) for the wristpin (98). The crown is coupled to the skirt and includes a lower surface in facing relation to the upper surface. The lower surface of the crown and the upper surface define a lubrication cavity (46). The top portion includes at least one inlet hole (84) adapted to supply a lubricant from the skirt cavity to the lubrication cavity. The top portion includes at least one lubrication hole (90) adapted to supply the lubrication cavity to the bearing surface and the wristpin.

WO 03/098003 A1